

FABRICS - TECHNICAL DATA SHEETPRODUCT NAME: **TESSA**COLLECTION: **TESSA****TECHNICAL DATA****BASIC INFORMATION**

Width usable (+/-)	140 cm
Weight (+/-)	500 g/m ²
Minimum order	0.1 m
Width total (+/-)	140 cm
Roll length (+/-)	35 m

ABRASION RESISTANCE

Standard	ISO 12 497-2
Result	>75 000 martindale cycles

COLOUR FASTNESS TO LIGHT

Standard	ISO 105-B02
Result	4

COLOUR FASTNESS TO RUBBING


Standard	EN ISO 105 X12
Wet friction	4-5
Dry friction	4-5

COMPOSITION

Polyester	95%
Acrylic	5%

SHRINKAGE

Standard	EN ISO 675
Wet	1%

SEAM SLIPPAGE	
Standard	EN ISO 13 936-2
Weft	2,4 mm
Warp	2,3 mm
PILLING	
Standard	EN ISO 12945
Result	4-5
MAINTENANCE	
	

Iron on reverse.
Dry in shade.

APPLICATIONS / PARAMETERS

APPLICATION	
Upholstery	
Decorative	
PARAMETERS	
Oeko-Tex Standard 100 class II	
Protective finish	
Teflon	

BEFORE YOU ORDER

ADDITIONAL REMARKS

1. Colour shades may vary slightly between production lots.
2. Information presented on this website does not constitute a trade offer.
3. Product technical parameters contained in the safety data sheet are based on the manufacturer's data.
4. Data on maintenance (cleaning methods) pertains to the fabrics we sell, not to finished products comprising different elements.
5. Before cutting the fabric, please verify the quantity delivered, quality of materials and conformity with the order.
6. With complete rolls of textiles, the length may differ slightly from the value declared.
7. In case of any doubts regarding the use of our products, visit the TIPS section at www.dekoma.eu or contact us directly.
8. Colours of products presented on this website may differ from the actual colours.

9. Due to the specific character of the production process, the parameters provided i.e. width, height, grammage, and repeat may differ slightly from the values declared.